# NSN 5925-00-139-9705

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-139-9705

# Body Style:

Multipole-single actuator type

# Mounting Slot Width:

0.203 inches

# Body Length:

6.310 inches

## Body Width:

2.750 inches

## **Body Height:**

3.510 inches

#### **Case Material:**

#### Plastic

Center To Center Distance Between Terminals Parallel To Length:

#### 5.125 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 1.375 inches

**Unthreaded Mounting Hole Diameter:** 

0.193 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.880 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.173 inches

#### **Boss Height:**

0.140 inches

#### **Pole Quantity:**

2

## Mounting Facility Type And Quantity:

4 slot and 2 unthreaded hole

## Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### Trip Release Method:

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations

Circuit Breaker - Page 2 of 2



# Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

## **Reset Method:**

Manual

# Main Contact Tripping Mechanism Type:

Trip free

# Manual Actuator Type And Quantity:

1 toggle

# **Actuator Function:**

Trip-reset

# Actuator Position Designation:

At pole one

# Inclosure Protection Type For Which Designed:

Fungus resistant

# Trip Release Ambient Tempurature Rating:

40.0 degrees celsius all locations

# Frequency In Hertz:

60.0 all locations

# Terminal Type And Quantity:

4 compression

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

## Fiig:

A030a0