NSN 5925-00-144-0434

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-144-0434

| Body Style: |
|--|
| Single pole type |
| Overall Length: |
| 2.000 inches |
| Body Width: |
| 1.188 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| 1.156 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.188 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.563 inches |
| Mounting Surface To Terminal End Distance: |
| 1.266 inches |
| Pole Quantity: |
| 1 |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Storage Type: |
| General purpose warehouse |
| Maximum Continuous Load Current Rating Per Pole: |
| 10.0 amperes dc single location |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 30.0 dc single location |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 600.0 dc single location |
| Circuit Protection Type: |
| Overcurrent single location |
| Trip Release Method: |
| Magnetic single location |
| Trip Release Characteristic: |
| Time delay single location |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 125.0 single location |
| Reset Method: |
| |
| Main Contact Tripping Mechanism Type: |
| Trip free |

NSN 5925-00-144-0434

Circuit Breaker - Page 2 of 2



| Manual Actuator Type And Quantity: |
|--|
| 1 push button |
| Actuator Function: |
| Reset |
| Actuator Position Designation: |
| At pole one |
| Internal Trip Release Configuration: |
| Series trip single location |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 30.000 at 200 pct single location |
| Inclosure Protection Type For Which Designed: |
| Dustproof |
| Terminal Type And Quantity: |
| 2 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |