

View Online at <https://aerobasegroup.com/nsn/5925-00-144-0466>

**Body Style:**

Single pole type

**Body Length:**

2.203 inches

**Body Width:**

0.766 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.812 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.812 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

1.406 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 threaded hole

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

80.0 amperes ac single location and 80.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac single location and 30.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

900.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

130.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.164 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

30.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Dustproof

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Frequency In Hertz:**

60.0 single location

**Unpackaged Unit Weight:**

1.850 ounces

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0