NSN 5925-00-148-2832

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-148-2832

Body Style:

Multipole-single actuator type

Bushing Length:

Between 0.250 inches and 0.312 inches

Body Length:

Between 1.187 inches and 1.249 inches

Body Width:

2.000 inches

Body Height:

3.105 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.625 inches

Center To Center Distance Between Terminals Parallel To Width:

0.500 inches

Fragility Factor:

Moderately rugged

Pole Quantity:

- 3
- Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 all locations

Reset Method:

Manual

NSN 5925-00-148-2832

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 push-pull **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two Internal Trip Release Configuration: Series trip all locations Thread Size: 0.469 inches Trip Delay Time In Seconds Per Rated Continuous Current: 2.000 at 200 pct all locations and 20.000 at 200 pct all locations **Inclosure Protection Type For Which Designed:** Shockproof and vibrationproof **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius all locations **Frequency In Hertz:** 400.0 all locations **Unpackaged Unit Weight:** 0.375 pounds **Thread Series Designator:** Uns **Terminal Type And Quantity:** 6 screw Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0