NSN 5925-00-153-4917

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-153-4917

View Online at https://aerobasegroup.com/nsn/5925-00-153-4917
Body Style:
Multipole-multiple actuator type
Mounting Slot Width:
0.563 inches
Body Length:
3.500 inches
Body Width:
3.000 inches
Body Height:
2.375 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
2.781 inches
Center To Center Distance Between Terminals Parallel To Width:
1.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.230 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.000 inches
Boss Height:
0.187 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
6 slot
Maximum Continuous Load Current Rating Per Pole:
70.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
10000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
100.0 all locations
Reset Method:

Manual

NSN 5925-00-153-4917 Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
35.000 at 200 pct all locations and 100.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0