NSN 5925-00-153-4962



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-153-4962 **Body Style:** Single pole type **Body Length:** 3.875 inches **Body Width:** 1.000 inches **Body Height:** 2.922 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Boss Height:** 0.187 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location **Trip Release Characteristic:** Instantaneous single location and time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Actuator Function:

Trip-reset

NSN 5925-00-153-4962

Circuit Breaker - Page 2 of 2



A	D	D	
Actuator	Position	Design	nation:
totaato.		200.91	iatioii.

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct single location and 150.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Tempurature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

600.0 single location

Terminal Type And Quantity:

1 compression and 1 clip

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0