## NSN 5925-00-154-0275

Circuit Breaker - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5925-00-154-0275

Maximum Continuous Load Current Rating Per Pole: 30.0 amperes ac all locations Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method: Magnetic-hydraulic all locations
30.0 amperes ac all locations  Operating Voltage Type And Rating Per Pole In Volts:  120.0 ac all locations  Circuit Protection Type:  Overcurrent all locations  Trip Release Method:
Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac all locations Circuit Protection Type: Overcurrent all locations Trip Release Method:
120.0 ac all locations  Circuit Protection Type:  Overcurrent all locations  Trip Release Method:
Circuit Protection Type:  Overcurrent all locations  Trip Release Method:
Overcurrent all locations  Trip Release Method:
Trip Release Method:
•
Magnetic-hydraulic all locations
Trip Release Characteristic:
Time delay all locations
Reset Method:
Manual
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
400.0 all locations
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0