

View Online at <https://aerobasegroup.com/nsn/5925-00-154-0372>

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.188 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

300.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 dc single location

Circuit Protection Type:

Reverse current single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Nontrip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

0.060 at 125 pct single location and 0.025 at 200 pct single location and 0.015 at 300 pct single location

Inclosure Protection Type For Which Designed:

Dustproof

Terminal Type And Quantity:

2 screw and 2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0