

View Online at <https://aerobasegroup.com/nsn/5925-00-156-4044>

Body Style:

Single pole type

Overall Length:

3.156 inches

Body Width:

1.875 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.062 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.406 inches

End Application:

Mrap - m-atv socom

Mounting Surface To Terminal End Distance:

1.312 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

150.0 amperes ac and 150.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

110.0 ac and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

900.0 ac and 900.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

130.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

6.000 at 200 pct and 50.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Unpackaged Unit Weight:

5.000 ounces

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0