NSN 5925-00-159-0267

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-159-0267

Overall Length:
6.000 inches
Overall Height:
3.968 inches
Overall Width:
1.375 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.188 inches
Pole Quantity:
1
Arc Quenching Method:
Deion
Mounting Facility Type And Quantity:
2 unthreaded hole
Maximum Continuous Load Current Rating Per Pole:
25.0 amperes ac single location and 25.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
125.0 ac single location and 125.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
5000.0 ac single location and 5000.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
122.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Trip Delay Time In Seconds Per Rated Continuous Current:
150.000 at 125 pct single location and 3600.000 at 125 pct single location and 18.000 at 200 pct single location and 105.000 at 200 pct
single location and 7.500 at 300 pct single location and 26.000 at 300 pct single location

Special Features:

Mtg holes diagonallyspaced on 0.812 in. By 4.843 in. Centers

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

NSN 5925-00-159-0267

Circuit Breaker - Page 2 of 2



Precious Material:
Silver
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0