## NSN 5925-00-159-1522

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-159-1522 **Overall Length:** 9.438 inches **Overall Height:** 4.781 inches **Overall Width:** 4.469 inches **Case Material:** Plastic Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 8.063 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.500 inches **Pole Quantity: Arc Quenching Method: Mounting Facility Type And Quantity:** 4 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 500.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 15000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 1400.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Reset

**Thread Size:** 0.190 inches

## NSN 5925-00-159-1522

Circuit Breaker - Page 2 of 2

Fiig: A030a0



Special Features:
Includes terminal hardware to modify breaker for front and/or back connected
Frequency In Hertz:
60.0 all locations
Thread Series Designator:
Unf
Terminal Type And Quantity:
6 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No