

View Online at <https://aerobasegroup.com/nsn/5925-00-163-0998>

Body Style:

Multipole-single actuator type

Bushing Length:

0.375 inches

Body Length:

2.188 inches

Body Width:

0.760 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.438 inches

Center To Center Distance Between Terminals Parallel To Width:

0.625 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.188 inches

Mounting Surface To Terminal End Distance:

2.312 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 threaded bushing

Maximum Continuous Load Current Rating Per Pole:

1.0 amperes ac all locations and 30.1 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations and 24.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations and 2000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Relay trip all locations

Thread Size:

0.164 inches

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0