## NSN 5925-00-166-8290

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-166-8290 **Body Length:** 6.000 inches **Body Width:** 2.219 inches **Body Height:** 2.530 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Width:** 0.739 inches **Boss Height:** 0.188 inches **Pole Quantity: Mounting Facility Type And Quantity:** 3 terminal **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 3 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** 

At each pole

**External Actuator Linkage Arrangement:** 

One, two, and three linked

## NSN 5925-00-166-8290

Circuit Breaker - Page 2 of 2



## Trip Delay Time In Seconds Per Rated Continuous Current:

360.000 at 200 pct all locations

**Trip Release Ambient Tempurature Rating:** 

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

**Terminal Type And Quantity:** 

3 clip and 3 compression

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0