

View Online at <https://aerobasegroup.com/nsn/5925-00-168-1459>

Thread Pitch Diameters:

+0.1177/+0.1214 inches

Body Style:

Multipole-multiple actuator type

Body Length:

Between 2.520 inches and 2.540 inches

Body Width:

Between 1.520 inches and 1.540 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.930 inches and 1.950 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.720 inches and 0.740 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.050 inches and 2.070 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.720 inches and 0.740 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.120 inches and 0.140 inches

Mounting Surface To Terminal End Distance:

Between 2.430 inches and 2.570 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac all locations and 35.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations and 50.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations and 2000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.200 at 200 pct all locations and 1.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Explosion proof and shock resistant

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

0.547 pounds

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0