

View Online at <https://aerobasegroup.com/nsn/5925-00-168-1459>

**Thread Pitch Diameters:**

+0.1177/+0.1214 inches

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

Between 2.520 inches and 2.540 inches

**Body Width:**

Between 1.520 inches and 1.540 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.930 inches and 1.950 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.720 inches and 0.740 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.050 inches and 2.070 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.720 inches and 0.740 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.120 inches and 0.140 inches

**Mounting Surface To Terminal End Distance:**

Between 2.430 inches and 2.570 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 threaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

35.0 amperes ac all locations and 35.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations and 50.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations and 2000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One and two linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.200 at 200 pct all locations and 1.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Explosion proof and shock resistant

**Frequency In Hertz:**

60.0 all locations

**Unpackaged Unit Weight:**

0.547 pounds

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

4 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0