NSN 5925-00-168-8598

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-168-8598

Body Style:
Multipole-multiple actuator type
Body Length:
3.730 inches
Body Width:
3.060 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
3.060 inches
Center To Center Distance Between Terminals Parallel To Width:
1.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length
2.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.030 inches
Boss Height:
0.160 inches
Mounting Surface To Terminal End Distance:
3.250 inches
Pole Quantity:
3
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
6 threaded hole
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
70.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
208.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1500.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic-hydraulic all locations

Time delay all locations

NSN 5925-00-168-8598 Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
150.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
3 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, and three linked
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.130 at 200 pct all locations and 1.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
1.770 pounds
Thread Series Designator:
Unc
Terminal Type And Quantity:
6 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0