NSN 5925-00-172-5070

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-172-5070 **Body Style:** Multipole-multiple actuator type **Body Length:** 3.875 inches **Body Width:** 4.000 inches **Body Height:** 2.359 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 1.000 inches **Boss Height:** 0.187 inches **Pole Quantity: Mounting Facility Type And Quantity:** 8 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 30.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 4 toggle

Trip-reset

Actuator Function:

NSN 5925-00-172-5070

Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One, two, three, and four linked
Internal Trip Release Configuration:
Series trip all locations
Trip Delay Time In Seconds Per Rated Continuous Current:
15.000 at 200 pct all locations and 120.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Fungus resistant
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
4 clip and 4 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0