

View Online at <https://aerobasegroup.com/nsn/5925-00-173-5463>

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

90.0 amperes ac single location and 90.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

900.0 ac single location and 900.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Thread Size:

0.190 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

15.000 at 200 pct single location and 50.000 at 200 pct single location and 0.600 at 400 pct single location and 5.000 at 400 pct single location

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0