NSN 5925-00-173-5873

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-173-5873 **Body Style:** Single pole type **Body Length:** 4.750 inches **Body Width:** 1.025 inches **Body Height:** 2.830 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length: 4.313** inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 2.750 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 50.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle

Reset

Actuator Function:

NSN 5925-00-173-5873

Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
35.000 at 200 pct single location
Frequency In Hertz:
60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0