

View Online at <https://aerobasegroup.com/nsn/5925-00-174-0262>

Body Style:

Single pole type

Bushing Length:

0.380 inches

Body Length:

1.622 inches

Body Width:

0.625 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.906 inches

Switch Contact Arrangement:

Single pole, double throw

Mounting Surface To Terminal End Distance:

1.656 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Ultimate Trip Time Per Pole In Seconds:

0.005 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Switch Location And Position Designation:

Internal at pole one

Inclosure Protection Type For Which Designed:

Hermetically sealed

Switch Terminal Type:

Wire hook

Switch Current Rating And Type In Amps:

0.5 ac and 0.5 dc

Switch Voltage Rating And Type In Volts:

120.0 ac and 50.0 dc

Frequency In Hertz:

60.0 single location

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0