

View Online at <https://aerobasegroup.com/nsn/5925-00-174-0434>

**Overall Length:**

24.000 inches

**Overall Height:**

19.750 inches

**Overall Width:**

13.000 inches

**Unthreaded Mounting Hole Diameter:**

0.563 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

13.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

8.000 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

480.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

25000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 rotary

**Actuator Function:**

Reset

**Special Features:**

Auxiliary switch included, trips instantaneously at 2.500 amps

**Reference Number Differentiating Characteristics:**

As differentiated by the pole, ac rating, interrupting capacity, circuit protection, tripping current, o/a dim, mtg holes, terminals and short time delay setting 1, 280 amp, time band no. 3

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0