## NSN 5925-00-174-0434

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-174-0434 **Overall Length:** 24.000 inches **Overall Height:** 19.750 inches Overall Width: 13.000 inches **Unthreaded Mounting Hole Diameter:** 0.563 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 13.000 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 8.000 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 6 unthreaded hole **Maximum Continuous Load Current Rating Per Pole:** 480.0 amperes dc all locations **Operating Voltage Type And Rating Per Pole In Volts:** 250.0 dc all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 25000.0 dc all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Time delay all locations **Reset Method: Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 rotary

**Actuator Function:** 

Reset

**Special Features:** 

Auxiliary switch included, trips instantaneously at 2.500 amps

## **Reference Number Differentiating Characteristics:**

As differentiated by the pole, ac rating, interrupting capacity, circuit protection, tripping current, o/a dim, mtg holes, terminals and short time delay setting 1, 280 amp, time band no. 3

## NSN 5925-00-174-0434

Circuit Breaker - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0