

View Online at <https://aerobasegroup.com/nsn/5925-00-174-3308>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

17.688 inches

**Overall Height:**

4.688 inches

**Overall Width:**

8.250 inches

**Case Material:**

Plastic

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded hole

**Thready Qty Per Inch (tpi):**

16

**Maximum Continuous Load Current Rating Per Pole:**

125.0 amperes ac all locations and 125.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac all locations and 10000.0 dc all locations

**Circuit Protection Type:**

Undervoltage third location

**Trip Release Method:**

Thermal all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip w/separate reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

108.000 at 200 pct all locations and 500.000 at 200 pct all locations

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0