

View Online at <https://aerobasegroup.com/nsn/5925-00-174-3308>

Body Style:

Rectangular dimensional envelope

Overall Length:

17.688 inches

Overall Height:

4.688 inches

Overall Width:

8.250 inches

Case Material:

Plastic

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Thready Qty Per Inch (tpi):

16

Maximum Continuous Load Current Rating Per Pole:

125.0 amperes ac all locations and 125.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Undervoltage third location

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip w/separate reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

108.000 at 200 pct all locations and 500.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0