NSN 5925-00-174-6327

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-174-6327

Body Style:

Multipole-single actuator type

Body Length:

5.950 inches

Body Width:

4.150 inches

Body Height:

3.370 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.000 inches

Center To Center Distance Between Terminals Parallel To Width:

1.350 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.445 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.350 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.120 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

NSN 5925-00-174-6327

Circuit Breaker - Page 2 of 2



Trip Release Characteristic: Instantaneous all locations and time delay all locations Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 125.0 all locations **Ultimate Trip Time Per Pole In Seconds:** 90.000 all locations and 3600.000 all locations **Reset Method:** Manual Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 1 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At pole two Trip Delay Time In Seconds Per Rated Continuous Current: 16.000 at 200 pct all locations and 45.000 at 200 pct all locations Inclosure Protection Type For Which Designed: General purpose **Trip Release Ambient Tempurature Rating:** 25.0 degrees celsius all locations **Frequency In Hertz:** 60.0 all locations **Terminal Type And Quantity:** 6 screw Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig:

A030a0