

View Online at <https://aerobasegroup.com/nsn/5925-00-174-6337>

Body Style:

Multipole-single actuator type

Body Length:

9.375 inches

Body Width:

4.125 inches

Body Height:

3.812 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

7.250 inches

Center To Center Distance Between Terminals Parallel To Width:

1.376 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.063 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.250 inches

Pole Quantity:

3

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

100.0 amperes ac all locations and 100.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

15000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Inclosure Protection Type For Which Designed:

Salt spray proof and shockproof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0