

View Online at <https://aerobasegroup.com/nsn/5925-00-174-8780>

Body Style:

Rectangular dimensional envelope

Overall Length:

24.000 inches

Overall Height:

13.000 inches

Overall Width:

13.000 inches

Unthreaded Mounting Hole Diameter:

0.562 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

6 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

640.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

40000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Automatic

Manual Actuator Type And Quantity:

1 rotary

Auxiliary Switch Function And Quantity:

1 control

Adjustable Trip Setting Current Range Per Pole In Amps:

+960.0 to 1600.0 ac all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

20.000 at 200 pct all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 bus bar

Reference Number Differentiating Characteristics:

As differentiated by pole quantity, continuous load current per pole, operating voltage type and rating per pole in volts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0