

View Online at <https://aerobasegroup.com/nsn/5925-00-174-8780>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

24.000 inches

**Overall Height:**

13.000 inches

**Overall Width:**

13.000 inches

**Unthreaded Mounting Hole Diameter:**

0.562 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

640.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

500.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

40000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Automatic

**Manual Actuator Type And Quantity:**

1 rotary

**Auxiliary Switch Function And Quantity:**

1 control

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+960.0 to 1600.0 ac all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

20.000 at 200 pct all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 bus bar

**Reference Number Differentiating Characteristics:**

As differentiated by pole quantity, continuous load current per pole, operating voltage type and rating per pole in volts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0