

View Online at <https://aerobasegroup.com/nsn/5925-00-174-8792>

**Unthreaded Mounting Hole Diameter:**

0.562 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

8 unthreaded hole

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

1200.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

50000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Automatic

**Manual Actuator Type And Quantity:**

1 rotary

**Actuator Function:**

Trip-reset

**Auxiliary Switch Function And Quantity:**

1 control

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+1800.0/+2800.0 dc all locations

**Terminal Type And Quantity:**

6 bus bar

**Reference Number Differentiating Characteristics:**

As differentiated by pole quantity, continuous load current rating per pole, operating voltage type and rating per pole in volts

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0