

View Online at <https://aerobasegroup.com/nsn/5925-00-174-8792>

Unthreaded Mounting Hole Diameter:

0.562 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

8 unthreaded hole

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

1200.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

50000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Automatic

Manual Actuator Type And Quantity:

1 rotary

Actuator Function:

Trip-reset

Auxiliary Switch Function And Quantity:

1 control

Adjustable Trip Setting Current Range Per Pole In Amps:

+1800.0/+2800.0 dc all locations

Terminal Type And Quantity:

6 bus bar

Reference Number Differentiating Characteristics:

As differentiated by pole quantity, continuous load current rating per pole, operating voltage type and rating per pole in volts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0