## NSN 5925-00-175-2595

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-175-2595

New Online at https://aerobasegroup.com/hsr/3923-00-173-2393
Overall Length:
2.000 inches
Overall Height:
1.281 inches
Overall Width:
1.188 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.188 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 unthreaded hole
Maximum Continuous Load Current Rating Per Pole:
15.0 amperes ac single location and 15.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
30.0 ac single location and 30.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
300.0 ac single location and 300.0 dc single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
113.0 single location
Reset Method:
Automatic
Main Contact Tripping Mechanism Type:
Trip free
Trip Delay Time In Seconds Per Rated Continuous Current:
200.000 at 125 pct single location and 6.500 at 200 pct single location and 1.600 at 300 pct single location
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:

## NSN 5925-00-175-2595

Circuit Breaker - Page 2 of 2

Demilitarization:

No

Fiig:

A030a0

