

View Online at <https://aerobasegroup.com/nsn/5925-00-175-2664>

Overall Length:

3.000 inches

Overall Height:

3.219 inches

Overall Width:

1.000 inches

Case Material:

Plastic

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Thread Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac single location and 35.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

24.0 ac single location and 24.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

4000.0 ac single location and 4000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

100.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Thread Size:

0.164 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

300.000 at 125 pct single location and 10.000 at 200 pct single location and 100.000 at 200 pct single location and 2.000 at 300 pct single location and 22.000 at 300 pct single location

Trip Release Ambient Temperature Rating:

50.0 degrees celsius single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0