NSN 5925-00-175-2664



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-175-2664 **Overall Length:** 3.000 inches **Overall Height:** 3.219 inches Overall Width: 1.000 inches **Case Material: Plastic Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 35.0 amperes ac single location and 35.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 24.0 ac single location and 24.0 dc single location **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 4000.0 ac single location and 4000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 100.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type: Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:** Trip-reset **Thread Size:** 0.164 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

300.000 at 125 pct single location and 10.000 at 200 pct single location and 100.000 at 200 pct single location and 2.000 at 300 pct single location and 22.000 at 300 pct single location

Trip Release Ambient Tempurature Rating:

50.0 degrees celsius single location

NSN 5925-00-175-2664

Circuit Breaker - Page 2 of 2



Thread Series Designator:
Unc
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0