

View Online at <https://aerobasegroup.com/nsn/5925-00-175-5222>

Body Style:

Single pole type

Bushing Length:

0.125 inches

Body Length:

2.187 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.125 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.843 inches

Mounting Surface To Terminal End Distance:

2.000 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

35.0 amperes ac single location and 35.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

30.0 ac single location and 30.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 ac single location and 2500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Automatic

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip w/separate reset

Actuator Position Designation:

At pole one

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

55.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A030a0