

View Online at <https://aerobasegroup.com/nsn/5925-00-177-2481>

Body Style:

Multipole-single actuator type

Body Length:

6.000 inches

Body Width:

2.234 inches

Body Height:

2.312 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

6.063 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Boss Height:

0.250 inches

Pole Quantity:

3

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac first location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 dc second location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

7500.0 ac first location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip w/separate reset

Actuator Position Designation:

At pole two

External Actuator Linkage Arrangement:

One, two, and three linked

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0