

View Online at <https://aerobasegroup.com/nsn/5925-00-187-8859>

Overall Length:

6.000 inches

Overall Height:

3.969 inches

Overall Width:

1.375 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.188 inches

Pole Quantity:

1

Arc Quenching Method:

Deion

Mounting Facility Type And Quantity:

2 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location and 15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac single location and 125.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac single location and 5000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

122.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip w/separate reset

Trip Delay Time In Seconds Per Rated Continuous Current:

170.000 at 125 pct single location and 3699.000 at 125 pct single location and 17.000 at 200 pct single location and 58.000 at 200 pct single location and 7.000 at 300 pct single location and 18.000 at 300 pct single location

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Special Features:

Mtg holes diagonally spaced on 0.812 by 4.844 in. Mtg centers

Terminal Type And Quantity:

1 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0