

View Online at <https://aerobasegroup.com/nsn/5925-00-187-8860>

**Overall Length:**

6.000 inches

**Overall Height:**

3.969 inches

**Overall Width:**

1.375 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.188 inches

**Pole Quantity:**

1

**Arc Quenching Method:**

Deion

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac single location and 20.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

125.0 ac single location and 125.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac single location and 5000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

122.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip w/separate reset

**Trip Delay Time In Seconds Per Rated Continuous Current:**

170.000 at 125 pct single location and 3600.000 at 125 pct single location and 17.000 at 200 pct single location and 58.000 at 200 pct single location and 7.000 at 300 pct single location and 18.000 at 300 pct single location

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Special Features:**

Mtg holes diagonally spaced on 0.812 by 4.844 in. Mtg centers

**Terminal Type And Quantity:**

1 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0