

NSN 5925-00-192-2990 Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-00-192-2990 **Body Style:** Multipole-multiple actuator type **Bushing Length:** 0.125 inches **Body Length:** 6.000 inches **Body Width:** 2.750 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.062 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.375 inches **Unthreaded Mounting Hole Diameter:** 0.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.500 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 3.375 inches

**Pole Quantity:** 

2

**Arc Quenching Method:** 

Magnetic blowout

**Mounting Facility Type And Quantity:** 

2 unthreaded hole

Storage Type:

General purpose warehouse

**Special Handling Feature:** 

Magnetic

**Maximum Continuous Load Current Rating Per Pole:** 

20.0 amperes ac all locations and 20.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:** 

240.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac all locations and 5000.0 dc all locations

**Circuit Protection Type:** 

Overcurrent all locations

**Trip Release Method:** 

Thermal-magnetic all locations

## **NSN 5925-00-192-2990** Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
30.000 at 200 pct all locations and 95.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Dustproof and general purpose and fungus resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
3.000 pounds
Terminal Type And Quantity:
4 compression
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A030a0