

View Online at <https://aerobasegroup.com/nsn/5925-00-192-5792>

**Thread Pitch Diameters:**

+0.1177/+0.1214 inches

**Body Style:**

Multipole-single actuator type

**Body Length:**

2.000 inches

**Body Width:**

2.265 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.530 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

1.660 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.130 inches

**Mounting Surface To Terminal End Distance:**

2.000 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

6 threaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

3500.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic-hydraulic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

2.000 at 200 pct all locations and 20.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Hermetically sealed and shock resistant and vibration resistant

**Switch Terminal Type:**

Quick disconnect, male

**Switch Current Rating And Type In Amps:**

10.0 ac and 5.0 dc

**Switch Voltage Rating And Type In Volts:**

250.0 ac and 30.0 dc

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Unpackaged Unit Weight:**

6.600 ounces

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0