

View Online at <https://aerobasegroup.com/nsn/5925-00-196-3729>

Body Style:

Single pole type

Body Length:

2.300 inches

Body Width:

0.750 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.680 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.810 inches

Switch Contact Arrangement:

Single pole, double throw

Boss Height:

0.125 inches

Mounting Surface To Terminal End Distance:

2.500 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

60.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

36.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.187 inches

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

3.000 at 200 pct single location and 15.000 at 200 pct single location

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

5.0 ac

Switch Voltage Rating And Type In Volts:

125.0 ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0