

View Online at <https://aerobasegroup.com/nsn/5925-00-196-3742>

Body Style:

Multipole-multiple actuator type

Body Length:

2.300 inches

Body Width:

Between 1.500 inches and 1.560 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.670 inches and 1.690 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.720 inches and 0.760 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.800 inches and 1.820 inches

Switch Contact Arrangement:

Single pole, double throw

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.720 inches and 0.760 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.115 inches and 0.135 inches

Mounting Surface To Terminal End Distance:

Between 1.845 inches and 1.905 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Switch Location And Position Designation:

Internal between pole one and two

Trip Delay Time In Seconds Per Rated Continuous Current:

0.016 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Vibration resistant

Switch Terminal Type:

Pin

Switch Current Rating And Type In Amps:

5.0 ac

Switch Voltage Rating And Type In Volts:

125.0 ac

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

8.000 ounces

Precious Material And Location:

Internal contacts silver and auxiliary terminals gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0