NSN 5925-00-209-0435

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-209-0435

Body Style:
Multipole-single actuator type
Body Length:
6.000 inches
Body Width:
4.469 inches
Body Height:
3.000 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
5.125 inches
Center To Center Distance Between Terminals Parallel To Width:
1.500 inches
Unthreaded Mounting Hole Diameter:
0.172 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
5.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.500 inches
Boss Height:
0.156 inches
Pole Quantity:
3
Mounting Facility Type And Quantity:
4 unthreaded hole
Maximum Continuous Load Current Rating Per Pole:
50.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
14000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
138.0 all locations
Reset Method:

Manual

NSN 5925-00-209-0435 Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
30.000 at 200 pct all locations and 100.000 at 200 pct all locations
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
3 clip and 3 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0