NSN 5925-00-221-8639

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-221-8639

Body Style:

Multipole-single actuator type

Body Length:

10.125 inches

Body Width:

4.125 inches

Body Height:

3.380 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

8.375 inches

Center To Center Distance Between Terminals Parallel To Width:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

7.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.750 inches

Boss Height:

0.240 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

225.0 amperes ac all locations and 225.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

22000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

NSN 5925-00-221-8639 Circuit Breaker - Page 2 of 2

Manual		
Main Contact Tripping Mechanism	Туре:	
Trip free		
Manual Actuator Type And Quantity	/ :	
1 toggle		
Actuator Function:		
Trip-reset		
Actuator Position Designation:		
Between pole one and two		
Internal Trip Release Configuration	:	
Series trip all locations		
Trip Delay Time In Seconds Per Ra	ted Continuous Current:	
0.024 at 200 pct all locations and 9.0	00 at 200 pct all locations	i
Inclosure Protection Type For Which	h Designed:	
General purpose		
Frequency In Hertz:		
60.0 all locations		
Terminal Type And Quantity:		
4 compression		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		
Fiig:		
A030a0		

