

View Online at <https://aerobasegroup.com/nsn/5925-00-223-0362>

Body Style:

Multipole-multiple actuator type

Body Length:

3.719 inches

Body Width:

3.052 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

3.063 inches

Center To Center Distance Between Terminals Parallel To Width:

1.031 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.031 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.156 inches

Mounting Surface To Terminal End Distance:

3.239 inches

Pole Quantity:

3

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1500.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

4.500 at 200 pct all locations and 17.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0