NSN 5925-00-224-7474

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-224-7474 **Body Style:** Single pole type **Bushing Length:** 0.250 inches **Body Length:** 0.781 inches **Body Width:** 0.593 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 0.500 inches **Mounting Surface To Terminal End Distance:** 1.343 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 threaded bushing Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 4.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 115.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 3500.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 138.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

1 push-pull

Manual Actuator Type And Quantity:

NSN 5925-00-224-7474

Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
nternal Trip Release Configuration:
Series trip single location
Thread Size:
0.438 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
1.500 at 200 pct single location and 30.000 at 200 pct single location
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Frequency In Hertz:
400.0 single location
Test Data Document:
31349-mil-c-5809 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Jns
Terminal Type And Quantity:
2 screw
Specification Data:
96906-ms3320 government standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4030a0