

View Online at <https://aerobasegroup.com/nsn/5925-00-226-0377>

Overall Length:

1.090 inches

Overall Height:

2.000 inches

Overall Width:

0.750 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.469 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location and 5.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location and 50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac single location and 6000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Trip Delay Time In Seconds Per Rated Continuous Current:

0.380 at 200 pct single location and 2.500 at 200 pct single location and 0.100 at 400 pct single location and 0.540 at 400 pct single location and 0.020 at 1000 pct single location and 0.120 at 1000 pct single location and 0.050 at 600 pct single location and 0.270 at 600 pct single location

Inclosure Protection Type For Which Designed:

Dustproof and corrosion resistant and explosion proof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0