NSN 5925-00-227-0387

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-227-0387

| Body Style: |
|------------------------------------------------------------------------------|
| Single pole type |
| Body Length: |
| Between 2.985 inches and 3.016 inches |
| Body Width: |
| 1.000 inches |
| Case Material: |
| Plastic |
| Center To Center Distance Between Terminals Parallel To Length: |
| Between 1.796 inches and 1.828 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 2.625 inches |
| Fragility Factor: |
| Moderately rugged |
| Boss Height: |
| 0.005 inches |
| Mounting Surface To Terminal End Distance: |
| Between 2.554 inches and 2.624 inches |
| Pole Quantity: |
| 1 |
| Arc Quenching Method: |
| Deion |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Storage Type: |
| General purpose warehouse |
| Thready Qty Per Inch (tpi): |
| 32 |
| Maximum Continuous Load Current Rating Per Pole: |
| 15.0 amperes ac single location and 15.0 amperes dc single location |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 125.0 ac single location and 32.0 dc single location |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 5000.0 ac single location and 5000.0 dc single location |
| Circuit Protection Type: |
| Overcurrent single location |
| Trip Release Method: |
| Thermal single location |
| Trip Release Characteristic: |
| Time delay single location |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 122.0 single location |

NSN 5925-00-227-0387 Circuit Breaker - Page 2 of 2



| Reset Method: |
|-------------------------------------------------------------------------|
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |
| 1 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At pole one |
| Internal Trip Release Configuration: |
| Series trip single location |
| Thread Size: |
| 0.164 inches |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 12.800 at 200 pct single location and 38.000 at 200 pct single location |
| Inclosure Protection Type For Which Designed: |
| General purpose |
| Trip Release Ambient Tempurature Rating: |
| 25.0 degrees celsius single location |
| Frequency In Hertz: |
| 60.0 single location |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material: |
| Silver |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 2 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |