NSN 5925-00-227-0396

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-00-227-0396

Body Style:
Single pole type
Overall Length:
3.156 inches
Body Width:
1.875 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.062 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.406 inches
Mounting Surface To Terminal End Distance:
1.156 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 threaded hole
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
60.0 amperes dc single location
Operating Voltage Type And Rating Per Pole In Volts:
30.0 dc single location
30.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
-
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 900.0 dc single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 900.0 dc single location Circuit Protection Type:
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 900.0 dc single location Circuit Protection Type: Overcurrent single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 900.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method:
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:900.0 dc single locationCircuit Protection Type:Overcurrent single locationTrip Release Method:Thermal single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:900.0 dc single locationCircuit Protection Type:Overcurrent single locationTrip Release Method:Thermal single locationTrip Release Characteristic:
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:900.0 dc single locationCircuit Protection Type:Overcurrent single locationTrip Release Method:Thermal single locationTrip Release Characteristic:Time delay single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:900.0 dc single locationCircuit Protection Type:Overcurrent single locationTrip Release Method:Thermal single locationTrip Release Characteristic:Time delay single locationUltimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:900.0 dc single locationCircuit Protection Type:Overcurrent single locationTrip Release Method:Thermal single locationTrip Release Characteristic:Time delay single locationUltimate Trip Rating Of Continuous Current Rating Per Pole In Percent:125.0 single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:900.0 dc single locationCircuit Protection Type:Overcurrent single locationTrip Release Method:Thermal single locationTrip Release Characteristic:Time delay single locationUltimate Trip Rating Of Continuous Current Rating Per Pole In Percent:125.0 single locationReset Method:
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:900.0 dc single locationCircuit Protection Type:Overcurrent single locationTrip Release Method:Thermal single locationTrip Release Characteristic:Time delay single locationUltimate Trip Rating Of Continuous Current Rating Per Pole In Percent:125.0 single locationReset Method:Manual
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:900.0 dc single locationCircuit Protection Type:Overcurrent single locationTrip Release Method:Thermal single locationTrip Release Characteristic:Time delay single locationUltimate Trip Rating Of Continuous Current Rating Per Pole In Percent:125.0 single locationReset Method:ManualManual

NSN 5925-00-227-0396 Circuit Breaker - Page 2 of 2



Actuator Function:
Reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.190 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
30.000 at 200 pct single location and 10.000 at 300 pct single location
Inclosure Protection Type For Which Designed:
Weatherproof
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Thread Series Designator:
Unf
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0