

View Online at <https://aerobasegroup.com/nsn/5925-00-229-7556>

Body Style:

Single pole type

Body Length:

1.781 inches

Body Width:

0.656 inches

Case Material:

Plastic

Switch Contact Arrangement:

Single pole, double throw

Mounting Surface To Terminal End Distance:

1.714 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

1.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

32.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2500.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

Ultimate Trip Time Per Pole In Seconds:

0.050 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.020 at 200 pct single location and 0.010 at 300 pct single location

Switch Terminal Type:

Tab, solder lug

Switch Current Rating And Type In Amps:

7.0 ac and 7.0 dc

Switch Voltage Rating And Type In Volts:

130.0 ac and 28.0 dc

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0