

View Online at <https://aerobasegroup.com/nsn/5925-00-232-3256>

Body Style:

Single pole type

Body Length:

2.000 inches

Body Width:

0.620 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.050 inches

Unthreaded Mounting Hole Diameter:

Between 0.219 inches and 0.229 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.590 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.045 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

8.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

12.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Automatic

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Actuator Position Designation:

At pole one

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0